
















# LITE

Res	Lens	Series	WDR	Model	Features	Image
2MP	Fixed 4mm	S+265	100dB	<a href="#">TC-NCL214</a>	POE, 1080P@30fps, WDR, NIR, ICR, 20m IR, IP67, 4mm lens	
2MP	Fixed 2.8mm	S+265	100dB	<a href="#">TC-NCL222</a>	POE, 1080P@30fps, WDR, NIR, ICR, 20m IR, IP66, 2.8mm lens	
2MP	Fixed 4mm	S+265 Starlight	100dB	<a href="#">TC-NCL214S</a>	POE, Starlight, 0.002Lux, 1080P@30fps, WDR, NIR, ICR, 20m IR, IP67, 4mm lens	
2MP	Fixed 2.8mm	S+265 Starlight	100dB	<a href="#">TC-NCL222S</a>	POE, Starlight, 0.002Lux, 1080P@30fps, WDR, NIR, ICR, 20m IR, IP66, 2.8mm lens	
2MP	Motorized 2.8-9mm	S+264	100dB	<a href="#">TC-NCL23MN</a>	POE, 1080P@20fps, WDR, NIR, ICR, Motorized 2.8-9mm, 30m IR, IP67,	
2MP	Motorized 2.8-9mm	S+264	100dB	<a href="#">TC-NCL24MN</a>	POE, 1080P@20fps, WDR, NIR, ICR, Motorized 2.8-9mm, 30m IR, IP66, 2.8mm lens	







# StarLight

Res	Lens	Series	WDR/IR Distance	Model	Features	Image
2MP	Motorized 3.6-10mm	S+265	140dB	<a href="#">TC-NC23MX</a>	PoE, 1080P@60fps, 1/1.8' Sony Sensor 0.0004lux, WDR 140dB, NIR, Dual ICR, 3.6-10mm Motorized Lens 50m IR range, IP67, Micro-SD slot, Audio 1/1, Alarm 1/0, USB, Full Metal	
2MP	Fixed 4mm	S+265	140dB	<a href="#">TC-NC294X</a>	PoE, 1080P@30fps, 1/1.8' Sony Sensor 0.0004lux, WDR, NIR, Dual ICR, 4mm Fixed Lens, 30m IR range, IP67, Audio 1/1, Alarm 1/0, USB, Metal+Plastic	
2MP	N/A	S+265	140dB	<a href="#">TC-NC27VX</a>	PoE, 1080P@60fps, 1/1.8" 2.0MP Exmor CMOS, H.265 Compression, Low illumination 0.0004Lux(Color), WDR 140dB, 4000V Lightning-proof, ABF, Audio 1/0, Alarm 1/0, without lens and bracket	
2MP	Fixed 4mm	S+265	140dB	<a href="#">TC-NC214S</a>	PoE, 1080P@30fps, 0.002lux, WDR, NIR, Dual ICR, 4mm lens, 20m IR Metal Housing, Cable-free design, TF Card Slot, IP67	
2MP	Fixed 2.8mm	S+265	140dB	<a href="#">TC-NC252S</a>	PoE, 1080P@30fps, 0.002lux, WDR, NIR, Dual ICR, 2.8mm lens, 20m IR Metal Housing, Cable-free design, TF Card Slot, Built-in Mic, IP66, IK10	
2MP	Fixed 2.8mm	S+265	140dB	TC-NC262S	PoE, 1080P@30fps, 0.002lux, WDR, NIR, BLC, Dual ICR, 2.8mm lens, 15m IR, Audio 1/1, Alarm 1/1, IP66, IK10	
2MP	Motorized 2.8-12mm	S+265	140dB	<a href="#">TC-NC23MS</a>	PoE, 1080P@30fps, 0.002lux, WDR, BLC, Dual ICR, Alarm 2/1, Audio 1/1, Metal Housing, MicroSD Slot, USB, 50m IR, IP67, Motorized Lens 2.8-12mm	
2MP	Motorized 2.8-12mm	S+265	140dB	<a href="#">TC-NC24MS</a>	PoE, 1080P@30fps, 0.002lux, WDR, BLC, Dual ICR, Alarm 2/1, Audio 1/1, Built-in Mic Metal Housing, MicroSD Slot, 30m IR, IP66, IK10, Motorized Lens 2.8-12mm	
2MP	Zoom 20X	S+265	100m	<a href="#">TC-NC2AS</a>	1080P@30fps, 1/2.8" CMOS Sensor, Low illumination 0.002lux, WDR 120dB, 20x Zoom White Light & 80~100m IR range, IP66, TVS 6000v, Lightning-proof 4000V Bracket model 2761N	

# Professional

Res	Lens	Series	WDR	Model	Features	Image
4MP	Fixed 4mm	S+265	120dB	<a href="#">TC-NC414</a>	PoE, 4MP(2560x1440)@30fps; WDR, NIR, BLC, Dual ICR, 4mm Lens, 25m IR, Smart VCA function, Metal Housing, Cable-free design, TF Card Slot, IP67	
4MP	Fixed 2.8mm	S+265	120dB	<a href="#">TC-NC452</a>	PoE, 4MP(2560x1440)@30fps; WDR, NIR, BLC, Dual ICR, 2.8mm Lens, 20m IR, Smart VCA function, Metal Housing, Cable-free design, TF Card Slot, Built-in Mic, IP66, IK10	
4MP	Motorized 2.8-12mm	S+265	120dB	<a href="#">TC-NC43M</a>	PoE, 4MP(2560x1440)@30fps; WDR, NIR, BLC, Dual ICR, Motorized Lens 2.8-12mm, 50m IR, Smart VCA function, Metal Housing, Audio 1/1, Alarm 1/0, MicroSD Slot, USB, IP67	
4MP	Motorized 2.8-12mm	S+265	120dB	<a href="#">TC-NC44M</a>	PoE, 4MP(2560x1440)@30fps; WDR, NIR, BLC, Dual ICR, Motorized Lens 2.8-12mm, 30m IR, Smart VCA function, Metal Housing Audio 1/1, Built-in Mic, Alarm 1/0, MicroSD Slot, 30m IR, IP66, IK10	
2MP	Fixed 4mm	S+264	100dB	<a href="#">TC-NC214</a>	PoE, 1080P@30fps, WDR, NIR, BLC, Dual ICR, 4mm Lens, 25m IR, Smart VCA function, Metal Housing, Cable-free design, TF Card Slot, IP67	
2MP	Fixed 2.8mm	S+264	100dB	<a href="#">TC-NC252</a>	PoE, 1080P@30fps, WDR, NIR, BLC, Dual ICR, 2.8mm Lens, 20m IR, Smart VCA function, Metal Housing, Cable-free design, TF Card Slot, Built-in Mic, IP66, IK10	
2MP	Varifocal 2.8-12mm	S+265	100dB	<a href="#">TC-NC23V</a>	PoE, 1080P@30fps; WDR, NIR, BLC, Dual ICR, Varifocal Lens 2.8-12mm, 50m IR, Smart VCA function, Metal Housing, Audio 1/1, Alarm 1/0, MicroSD Slot, USB, IP67	
2MP	Varifocal 2.8-12mm	S+265	100dB	<a href="#">TC-NC24V</a>	PoE, 1080P@30fps; WDR, NIR, BLC, Dual ICR, Varifocal Lens 2.8-12mm, 30m IR, Smart VCA function, Metal Housing Audio 1/1, Built-in Mic, Alarm 1/0, MicroSD Slot, 30m IR, IP66, IK10	
2MP	Motorized 2.8-12mm	S+265	120dB	<a href="#">TC-NC23M</a>	PoE, 1080P@30fps; WDR, NIR, BLC, Dual ICR, Motorized Lens 2.8-12mm, 50m IR, Smart VCA function, Metal Housing, Audio 1/1, Alarm 1/0, MicroSD Slot, USB, IP67	
2MP	Motorized 2.8-12mm	S+265	120dB	<a href="#">TC-NC24M</a>	PoE, 1080P@30fps; WDR, NIR, BLC, Dual ICR, Motorized Lens 2.8-12mm, 30m IR, Smart VCA function, Metal Housing Audio 1/1, Built-in Mic, Alarm 1/0, MicroSD Slot, 30m IR, IP66, IK10	

# PTZ

Res	Lens	Series	WDR	Model	Features	Image
4K	Fixed 2mm	S+265	120dB	<a href="#">TC-NC1261</a>	Panoramic Camera, PoE, 4K(4000 × 3072)@30fps Auto-tracking, Heat Map, Early-warning, Smart IR, IR Range: 10-20m, 3pcs IR + 3pcs White light, Built-in Mic and speaker, IP66, IK10	
2MP	Zoom 44X	S+265	IR 500~800m	<a href="#">TC-NH9844ISA-G</a>	Panoramic PTZ 180°, 1/1.8" Super Starlight CMOS sensor Panoramic image: 4K(4096×1800@30fps), single image: 1080P@60fps, Speed 0.1°~160°/s, Auto-tracking&Smart VCA, MicroSD Slot(128GB), TVS 6000V protection IP66 waterproof, Low Illumination: 0.0004Lux Wiper, Speaker, White Light, Laser up to 500~800m 360° panoramic model / Thermal model / 1000m Laser model	
2MP	Zoom 44X	S+265	IR 300m	<a href="#">TC-NH6244ISA-G</a>	1/1.8" Super Starlight CMOS sensor, 1080P@60fps, Speed 0.05°~400°/s, Auto-tracking&Smart VCA, MicroSD Slot(128GB), TVS 6000V protection IP66 waterproof, Low Illumination: 0.0004Lux Wiper, Speaker, White Light, Laser	
2MP	Zoom 4X	S+265	100dB	<a href="#">TC-NH3204IE</a>	1/2.8" Starlight sensor, 1080P@30fps, 2.8-12mm 4x optical zoom, -2~90°, Speed 0.1°~60°/s, MicroSD card(128GB), TVS 6000V protection; Built-in Gyro and Support Image Auto-flip; Low Illumination: 0.002Lux POE White light Speaker	
2MP	Zoom 33X	S+265	IR 180m	<a href="#">TC-NH6233I</a>	1/2.8" CMOS Sensor, 1080P@30fps Speed 0.05°~400°/s, MicroSD card(128GB) TVS 6000V protection; IP66 waterproof, -16~90°, Low Illumination: 0.002Lux	
2MP	20X	S+265	IR 100m	<a href="#">TC-NH6220IE-CP</a>	1/2.8" CMOS Sensor, 1080P@30fps Speed 0.05°~400°/s, MicroSD card(128GB) TVS 6000V protection, IP66 waterproof Low Illumination: 0.002Lux, POE+	

# NVR

Channel	Hard Drive	Special	Model	Features
4ch	1 HDD	S+264 PoE	<a href="#">TC-NR4004M7-P1</a>	4ch IP Camera Input, resolution up to 6MP, 4ch Sync playback; Bandwidth I/O: 40Mbps/40Mbps, Plug&Play with 4 PoE Interfaces, Support Camera Smart VCA,HDMI&VGA, 2 USB, Alarm I/O 0/1, 1 SATA(Up to 8TB) + <b>1TB</b>
8ch	2 HDD	S+264 PoE	<a href="#">TC-NR4008M7-P2</a>	8ch IP Camera Input, resolution up to 6MP, 8ch Sync playback; Bandwidth I/O: 80Mbps/80Mbps, Plug&Play with 8 PoE Interfaces, Support Camera Smart VCA, HDMI&VGA, 2 USB, Alarm I/O 0/1, 2 SATA(Up to 16TB) + <b>1TB</b>
16ch	2 HDD	S+264 PoE	<a href="#">TC-NR4016M7-P2</a>	16ch IP Camera Input, resolution up to 6MP, 16ch Sync playback; Bandwidth I/O: 128Mbps/64Mbps, Plug&Play with 8 PoE Interfaces, Support Camera Smart VCA, HDMI&VGAHDMI, 2 USB, Alarm I/O 0/1, 2 SATA(Up to 16TB)+ <b>2TB</b>
4ch	1 HDD	/	<a href="#">TC-NR4004M7-S1</a>	4ch IP Camera Input, 4ch Sync playback; Bandwidth:50Mbps, Support Camera Smart VCA HDMI&VGA, 1 SATA(Up to 4TB), Alarm I/O1/0+ <b>1TB</b>
8ch	2 HDD	H.264	<a href="#">TC-NR4008M7-S2</a>	8ch IP Camera Input, 8ch Sync playback; Bandwidth:50Mbps, Support Camera Smart VCA HDMI&VGA, 2 SATA(Up to 8TB), Alarm I/O1/0+ <b>1TB</b>
16ch	2 HDD	H.264	<a href="#">TC-NR4016M7-S2</a>	16ch IP Camera Input, 16ch Sync playback; Bandwidth I/O: 128Mbps/64Mbps HDMI&VGA, 2 SATA(Up to 8TB), Alarm I/O1/0 + <b>2TB</b>
5ch	1 HDD	S+265	<a href="#">TC-NR5005M7-S1</a>	5ch IP Camera Input, resolution up to 4K, 4ch Sync playback; Bandwidth I/O: 40Mbps/40Mbps, Support Camera Smart VCA 1SATA(up to 4TB), 1 HDMI&VGA, 2USB, Alarm I/O 0/1 + <b>1TB</b>
10ch	1 HDD	S+265	<a href="#">TC-NR5010M7-S1</a>	10ch IP Camera Input, resolution up to 4K, 4ch Sync playback; Bandwidth I/O: 60Mbps/60Mbps, Support Camera Smart VCA 1SATA(up to 4TB), 1 HDMI&VGA,2USB, Alarm I/O 0/1
20ch	1 HDD	S+265	<a href="#">TC-NR5020M7-S1</a>	20ch IP Camera Input, resolution up to 4K, 4ch Sync playback; Bandwidth I/O: 60Mbps/60Mbps, Support Camera Smart VCA 1SATA(up to 4TB), 1 HDMI&VGA,2USB, Alarm I/O 0/1
10ch	2 HDD	S+265	TC-NR5010M7-S2	10ch IP Camera Input, resolution up to 4K, 4ch Sync playback; Bandwidth I/O: 60Mbps/60Mbps, Support Camera Smart VCA 1SATA(up to 4TB), 1 HDMI&VGA,2USB, Alarm I/O 0/1

# NVR

Channel	Hard Drive	Special	Model	Features
20ch	2 HDD	S+265	<a href="#">TC-NR5020M7-S2-C</a>	20ch IP Camera Input, resolution up to 4K, 16ch Sync playback; Bandwidth I/O: 400Mbps/200Mbps, Support Camera Smart VCA 2SATA(up to 16TB), 1 HDMI&VGA, 2USB, Alarm I/O 0/1
20ch	4 HDD	S+265	<a href="#">TC-NR5020M7-S4</a>	20ch IP Camera Input, resolution up to 4K, 16ch Sync playback; Bandwidth I/O: 400Mbps/200Mbps, Support Camera Smart VCA 4SATA(up to 32TB), 1 HDMI&VGA, 2USB, Alarm I/O 16/4
40ch	4HDD	S+265	<a href="#">TC-NR5040M7-S4</a>	40ch IP Camera Input, resolution up to 4K, 16ch Sync playback; Bandwidth I/O: 400Mbps/200Mbps, Support Camera Smart VCA 4SATA(up to 32TB), 1 HDMI&VGA, 2USB, Alarm I/O 16/4
32ch	8 HDD	S+264	<a href="#">TC-NR4032M7-S8</a>	32ch IP Camera Input, 16ch Sync playback; Bandwidth I/O: 200Mbps/120Mbps, Support Camera Smart VCA HDMIx2, VGA Output, Alarm I/O: 16/4 RJ45x2(1000M), 8 SATA(Up to 32TB)
40ch	8 HDD	S+265 Raid	<a href="#">TC-NR5040M7-S8</a>	40ch IP Camera Input, resolution up to 4K, 16ch Sync playback; Bandwidth I/O: 400Mbps/200Mbps, Support Camera Smart VCA 8SATA(up to 64TB), 2 HDMI&VGA, 3USB, Alarm I/O 16/4 Support Raid 0,1,5,10
80ch	8 HDD	S+265 Raid	<a href="#">TC-NR5080M7-S8</a>	80ch IP Camera Input, resolution up to 4K, 16ch Sync playback; Bandwidth I/O: 400Mbps/200Mbps, Support Camera Smart VCA 8SATA(up to 64TB), 2 HDMI&VGA, 3USB, Alarm I/O 16/4 Support Raid 0,1,5,10
80ch	16 HDD	S+265 Raid, Hot Swap	<a href="#">TC-NR5080M7-E16</a>	80ch IP Camera Input, resolution up to 4K, 16ch Sync playback; Bandwidth I/O: 400Mbps/200Mbps, Support Camera Smart VCA 16SATA(up to 128TB), 2 HDMI&VGA, 3USB, Alarm I/O 16/4 Support Raid 0,1,5,10
160ch	16 HDD	S+265 Raid, Hot Swap	<a href="#">TC-NR5160M7-E16</a>	160ch IP Camera Input, resolution up to 4K, 16ch Sync playback; Bandwidth I/O: 400Mbps/200Mbps, Support Camera Smart VCA 16SATA(up to 128TB), 2 HDMI&VGA, 3USB; Alarm I/O 16/4 Support Raid 0,1,5,10